

View Online at <https://aerobasegroup.com/nsn/5305-01-340-5065>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.245 inches and 0.255 inches

**Fastener Length:**

Between 0.594 inches and 0.624 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 0.256 inches and 0.270 inches

**Head Height:**

Between 0.087 inches and 0.097 inches

**Internal Drive Style:**

Slot

**Material Accommodated Thickness:**

Between 0.145 inches and 0.155 inches

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Material:**

Steel comp 302 springsteel comp 301 stand-off or steel comp 302 stand-off or steel comp 302b stand-off or steel comp 303 stand-off or steel comp 303se stand-off or steel comp 304 stand-off or steel comp 304l stand-off or steel comp 305 stand-off or steel comp 308 stand-off or steel comp 309 stand-off or steel comp 309s stand-off or steel comp 310 stand-off or steel comp 310s stand-off or steel comp 314 stand-off or steel comp 316 stand-off or steel comp 316l stand-off or steel comp 317 stand-off or steel comp 321 stand-off or steel comp 347 stand-off or steel comp 348 stand-off or steel comp 384 stand-off or steel comp 385 stand-offiron alloy 660 fastener

**Material Specification:**

Ams 5732 assn standard single material response fastener

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**