Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-340-6193

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.680 inches
Fastener Length:
1.250 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.262 inches and 0.270 inches
Head Height:
Between 0.159 inches and 0.164 inches
First Diameter From Head:
Between 0.105 inches and 0.115 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.570 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.164 inches
Width Across Flats:
Between 0.141 inches and 0.143 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell c
Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Surface Treatment:
Passivate
Surface Treatment Specification:
Sps 03301, ty2, cage1246 mfr ref single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0