

View Online at <https://aerobasegroup.com/nsn/5305-01-340-6194>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.680 inches

**Fastener Length:**

1.579 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.262 inches and 0.270 inches

**Head Height:**

Between 0.159 inches and 0.164 inches

**First Diameter From Head:**

Between 0.105 inches and 0.115 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.899 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.164 inches

**Width Across Flats:**

Between 0.141 inches and 0.143 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Hardness Rating:**

80.0 rockwell c

**Minimum Yield Strength:**

30000 pounds per square inch

**Externally Relieved Body Diameter Quantity:**

1

**Color:**

Black

**Material:**

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924, cl4 military specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.