

View Online at <https://aerobasegroup.com/nsn/5305-01-340-6338>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.252 inches and 0.302 inches

Fastener Length:

Between 0.950 inches and 0.980 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.244 inches and 0.279 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740

Screw Surface Treatment:

Cadmium

Screw Surface Treatment Specification:

Qq-p-416 type 1 cl 3 federal specification single treatment response

Bearing Surface Of Head Surface Finish:

63.0 microinches

Shank Surface Finish:

32.0 microinches

Thread Surface Finish:

32.0 microinches

Thread Series Designator:

Unjc

Specification Data:

80205-nas1221 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0