NSN 5305-01-340-8568

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-340-8568

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.283 inches and 0.375 inches
Fastener Length:
Between 0.345 inches and 0.375 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.218 inches and 0.226 inches
Head Height:
Between 0.134 inches and 0.138 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.138 inches
Width Across Flats:
Between 0.109 inches and 0.111 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
33.0 rockwell c and 42.0 rockwell c
Minimum Yield Strength:
120000 pounds per square inch
Color:
Black
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5737 assn standard single material response
Surface Treatment:
Oxide
Surface Treatment Specification:
Mil-c-13924, cl3 military specification single treatment response
Thread Series Designator:
Unrc
Specification Data:

NSN 5305-01-340-8568

Socket Head Cap Screw - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
110
Fiig:

Shelf Life:

Mil-std (military Standard):

Mil-c-13924 spec.