

View Online at <https://aerobasegroup.com/nsn/5305-01-341-0715>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.290 inches and 0.340 inches

**Fastener Length:**

Between 0.490 inches and 0.510 inches

**Head Style:**

Headless (setscrew)

**Point Length:**

Between 0.170 inches and 0.200 inches

**Point Diameter:**

Between 0.165 inches and 0.175 inches

**Point Style:**

Dog

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.250 inches

**Width Across Flats:**

Between 0.125 inches and 0.127 inches

**Thready Qty Per Inch (tpi):**

28

**Hardness Rating:**

45.0 rockwell c and 53.0 rockwell c

**Material:**

Steel comp 4037 or steel comp 4140 or steel comp 8630 or steel comp 8740

**Material Specification:**

Aisi assn standard all material responses

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Mil-c-8837 ty2 cl3 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.