## NSN 5305-01-341-3069

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-341-3069 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.200 inches **Fastener Length:** 0.438 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches **First Diameter From Head:** Between 0.065 inches and 0.075 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.238 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.094 inches and 0.095 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Hardness Rating:** 80.0 rockwell c **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Surface Treatment: Passivate Surface Treatment Specification:** Sps 03301, ty2, cage12464 mfr ref single treatment response **Thread Series Designator:** Unc

Cha

Shelf Life:

N/a

## NSN 5305-01-341-3069

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0