## NSN 5305-01-341-3097

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-341-3097 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.219 inches and 0.281 inches **Fastener Length:** Between 0.719 inches and 0.784 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.344 inches and 0.406 inches **Head Height:** Between 0.156 inches and 0.219 inches **Shoulder Diameter:** 0.2485 inches first shoulder and 0.2495 inches first shoulder **Shoulder Length:** 0.500 inches first shoulder and 0.503 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: 0.125 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 43.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp xm-7 or steel comp 303 **Material Specification:** Astm a493 assn standard 1st material response or astm a582 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** 

Unc **She**l

Shelf Life:

N/a

## NSN 5305-01-341-3097

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0