## NSN 5305-01-341-4111

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-341-4111 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.363 inches **Fastener Length:** Between 1.410 inches and 1.440 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.360 inches and 0.374 inches **Head Height:** Between 0.115 inches and 0.125 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1578 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-341-4111

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0