

View Online at <https://aerobasegroup.com/nsn/5305-01-341-4684>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.203 inches

Fastener Length:

Between 0.343 inches and 0.375 inches

Head Style:

Pan

Head Diameter:

Between 0.357 inches and 0.373 inches

Head Height:

Between 0.122 inches and 0.132 inches

Washer Quantity:

2

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

55000 pounds per square inch

Secondary Washer Relationship To Primary Washer:

Not identical

Secondary Washer Style:

Flat

Primary Washer Outside Diameter:

0.334 inches

Secondary Washer Outside Diameter:

Between 0.338 inches and 0.348 inches

Primary Washer Style:

Split helical ring

Primary Washer Material Thickness:

0.047 inches

Secondary Washer Material Thickness:

Between 0.029 inches and 0.035 inches

Material:

Steel comp 1020 secondary washersteel comp 1020 primary washersteel fastener

Material Specification:

Mil-s-7952 military specification single material response secondary washermil-s-7952 military specification single material response primary washerastm a663 assn standard single material response fastener

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, ty2 cl2 federal specification single treatment response

Thread Series Designator:

Unf

Specification Data:

80205-nas1301 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-7952 spec.