NSN 5305-01-341-6716

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-341-6716

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.500 inches
Fastener Length:
2.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.735 inches and 0.750 inches
Head Height:
Between 0.616 inches and 0.650 inches
Locking Feature:
Strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.500 inches
Width Across Flats:
Between 0.375 inches and 0.379 inches
Thready Qty Per Inch (tpi):
13
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c fastener and 49.0 rockwell c fastener
Minimum Yield Strength:
155000 pounds per square inch
Product Name:
Navy special project
Color:
Black fastener
Material:
Plastic polyamide locking featuresteel fastener
Surface Treatment:
Oxide fastener
Surface Treatment Specification:
Mil-c-13924, cl3 military specification single treatment response fastener
Thread Series Designator:

Unrc

NSN 5305-01-341-6716

Socket Head Cap Screw - Page 2 of 2



80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.