

View Online at <https://aerobasegroup.com/nsn/5305-01-341-6725>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.363 inches

Fastener Length:

Between 0.847 inches and 0.878 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.360 inches and 0.374 inches

Head Height:

Between 0.115 inches and 0.125 inches

Locking Feature:

Patch threads or pellet threads or strip threads

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Internal Drive Style:

Torque-set ribbed

Thread Diameter:

0.190 inches

Grip Length:

Between 0.490 inches and 0.510 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c fastener and 40.0 rockwell c fastener

Surface Finish:

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

Material:

Plastic polyamide locking featuresteel comp 4140 fastener or steel comp e4340 fastener or steel comp 8740 fastener

Material Specification:

Mil-s-5626 military specification 1st material response fastener or mil-s-5000 military specification 2nd material response fastener or mil-s-6049 military specification 3rd material response fastener

Surface Treatment:

Cadmium fastener and chromate fastener

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Specification Data:

80205-nas1578 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.