## NSN 5305-01-341-7088

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-341-7088



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 1.069 inches and 1.193 inches Fastener Length: Between 1.193 inches and 1.250 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.231 inches and 0.279 inches Locking Feature: Patch **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Iron alloy 660 Locking Feature Material: Plastic polyamide **Screw Material Specification:** Ams 5737 assn standard single material response **Screw Surface Treatment:** Passivate **Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Bearing Surface Of Head Surface Finish:** 32.0 microinches **Thread Surface Finish:** 32.0 microinches **Thread Series Designator:** Unjc **Specification Data:**

80205-nas1189 professional/industrial association standard

## NSN 5305-01-341-7088

Machine Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A500d0

