## NSN 5305-01-341-8639

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-341-8639

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.969 inches and 2.125 inches
Fastener Length:
Between 2.031 inches and 2.125 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.221 inches and 0.226 inches
Head Height:
Between 0.074 inches and 0.086 inches
Internal Drive Style:
Cross recess type ii
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Steel comp 4140 or steel comp e4340
Screw Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1101 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A500d0

## NSN 5305-01-341-8639

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5626 spec.