NSN 5305-01-341-9159

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-341-9159

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.219 inches and 0.321 inches |
| Fastener Length: |
| Between 0.281 inches and 0.321 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.211 inches and 0.226 inches |
| Head Height: |
| Between 0.074 inches and 0.086 inches |
| Hole Diameter: |
| Between 0.034 inches and 0.042 inches |
| Internal Drive Style: |
| Torque set |
| Thread Diameter: |
| 0.138 inches |
| Hole Quantity: |
| 1 |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| Between 36.0 rockwell c and 40.0 rockwell c |
| Screw Material: |
| Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 |
| Screw Surface Treatment: |
| Cadmium and chromate |
| Screw Surface Treatment Specification: |
| Qq-p-416, ty2, cl2 federal specification single treatment response |
| Head Hole Configuration Style: |
| Round longitudinal hole |
| Bearing Surface Of Head Surface Finish: |
| 32.0 microinches |
| Thread Surface Finish: |
| 32.0 microinches |
| Color: |
| Black |
| |

NSN 5305-01-341-9159

Machine Screw - Page 2 of 2

A500d0



| Thread Series Designator: |
|--|
| Unjc |
| Specification Data: |
| 80205-nas1101 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Filg: |