

View Online at <https://aerobasegroup.com/nsn/5305-01-341-9159>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.219 inches and 0.321 inches

**Fastener Length:**

Between 0.281 inches and 0.321 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.211 inches and 0.226 inches

**Head Height:**

Between 0.074 inches and 0.086 inches

**Hole Diameter:**

Between 0.034 inches and 0.042 inches

**Internal Drive Style:**

Torque set

**Thread Diameter:**

0.138 inches

**Hole Quantity:**

1

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

Between 36.0 rockwell c and 40.0 rockwell c

**Screw Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416, ty2, cl2 federal specification single treatment response

**Head Hole Configuration Style:**

Round longitudinal hole

**Bearing Surface Of Head Surface Finish:**

32.0 microinches

**Thread Surface Finish:**

32.0 microinches

**Color:**

Black

**Thread Series Designator:**

Unjc

**Specification Data:**

80205-nas1101 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0