## NSN 5305-01-342-2718

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-342-2718

| Thread Class:  |
|--|
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.385 inches   |
| Fastener Length:   |
| 0.447 inches   |
| Head Style:  |
| Flat chamfer   |
| Head Diameter:   |
| 0.620 inches   |
| Head Height:   |
| 0.100 inches   |
| Shoulder Diameter:   |
| 0.250 inches first shoulder  |
|  |
| Shoulder Length:   |
| 0.140 inches first shoulder  |
| Internal Drive Style:  |
| Slot   |
| Thread Diameter:   |
| 0.190 inches   |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Shoulder Shape:  |
| Round first shoulder   |
| Material:  |
| Steel comp 4130  |
| Material Specification:  |
| Mil-s-6958 military specification single material response         |
| Surface Treatment:   |
| Cadmium  |
| Surface Treatment Specification:                                   |
| Qq-p-416, ty1, cl3 federal specification single treatment response |
| Thread Series Designator:  |
| Unf  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |

No

## NSN 5305-01-342-2718

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6958 spec.