NSN 5305-01-342-3675

Setscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-342-3675

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Fastener Length: |
| 0.650 inches |
| Head Style: |
| Pan no. 2 |
| Head Diameter: |
| Between 0.3650 inches and 0.3750 inches |
| Head Height: |
| Between 0.244 inches and 0.250 inches |
| Locking Feature: |
| Patch locking feature |
| Point Length: |
| 0.170 inches |
| Point Diameter: |
| 0.175 inches |
| Point Style: |
| Chamfer dog |
| Internal Drive Style: |
| Hexagon |
| End Application: |
| Used on abf334 ar5 |
| Thread Diameter: |
| 0.750 inches |
| Width Across Flats: |
| Between 0.1875 inches and 0.1900 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Point Chamfer Angle: |
| 45.0 degrees |
| Material: |
| Steel |
| Material Specification: |
| Ms16998-43 military standard single material response |
| Surface Treatment: |
| Phosphate zinc and oil |
| Surface Treatment Specification: |
| Mil-p-16232, type z, cl 1 military specification single treatment response and mil-std-3150 military standard single treatment response |
| Thread Series Designator: |

Unf

NSN 5305-01-342-3675

Setscrew - Page 2 of 2



| Shelf | Life: |
|-------|-------|
| NI/o | |

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-p-16232 spec.