

View Online at <https://aerobasegroup.com/nsn/5305-01-342-5176>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.200 inches and 0.250 inches

Fastener Length:

0.250 inches

Head Style:

Fillister

Head Diameter:

Between 0.490 inches and 0.518 inches

Head Height:

Between 0.194 inches and 0.211 inches

Locking Feature:

Patch or strip or pellet

Internal Drive Style:

Slot

Thread Diameter:

0.125 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

60000 pounds per square inch

Screw Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Locking Feature Material:

Plastic polyamide

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416, ty2 cl3 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0