

View Online at <https://aerobasegroup.com/nsn/5305-01-342-5176>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.200 inches and 0.250 inches

**Fastener Length:**

0.250 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.490 inches and 0.518 inches

**Head Height:**

Between 0.194 inches and 0.211 inches

**Locking Feature:**

Patch or strip or pellet

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.125 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

60000 pounds per square inch

**Screw Material:**

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

**Locking Feature Material:**

Plastic polyamide

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416, ty2 cl3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0