NSN 5305-01-342-9046

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-342-9046

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.447 inches |
| Fastener Length: |
| Between 1.807 inches and 1.837 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.752 inches and 0.762 inches |
| Grip Diameter: |
| Between 0.3740 inches and 0.3745 inches |
| Shank Unthreaded Hole Diameter: |
| 0.106 inches first hole and 0.111 inches first hole |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.375 inches |
| Grip Length: |
| Between 1.365 inches and 1.385 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 1.688 inches first hole |
| Product Name: |
| Navy special project |
| Material: |
| Stainless steel |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5305-01-342-9046

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

