## NSN 5305-01-343-1159

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-343-1159 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.533 inches and 0.625 inches **Fastener Length:** Between 0.595 inches and 0.625 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.159 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 33.0 rockwell c and 42.0 rockwell c Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unrf **Specification Data:** 80205-nas1351 professional/industrial association standard Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-343-1159

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0