## NSN 5305-01-343-4205

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-343-4205 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.110 inches and 0.125 inches **Fastener Length:** Between 0.360 inches and 0.390 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.250 inches and 0.265 inches **Head Height:** Between 0.240 inches and 0.260 inches Point Length: Between 0.063 inches and 0.093 inches **Point Diameter:** Between 0.068 inches and 0.078 inches **First Diameter From Head:** Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.162 inches and 0.182 inches Point Style: Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** 90.0 degrees Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

## NSN 5305-01-343-4205

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0