NSN 5305-01-343-7241

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-343-7241 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.594 inches **Fastener Length:** Between 1.267 inches and 1.297 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.515 inches and 0.566 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:**

Unit Of Measure:

N/a

Shelf Life:

80205-nas1581 professional/industrial association standard

NSN 5305-01-343-7241

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0