

View Online at <https://aerobasegroup.com/nsn/5305-01-344-0619>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.140 inches and 0.170 inches

Fastener Length:

Between 0.515 inches and 0.545 inches

Head Style:

Pan

Head Diameter:

0.335 inches

Head Height:

0.150 inches

Internal Drive Style:

Cross recess type 1

Material Accommodated Thickness:

Between 0.049 inches and 0.075 inches

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Color:

Black springblack fastener

Material:

Steel comp 302 spring or steel comp 302b spring or steel comp 303 spring or steel comp 303 plus x spring or steel comp 303se spring or steel comp 303cu spring or steel comp 303ma spring or steel comp 304 spring or steel comp 304l springaluminum alloy 7075 stand-offsteel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener

Material Specification:

Qq-a-225 federal specification single material response stand-offastm-a-493 assn standard all material responses fastener

Surface Treatment:

Oxide spring or passivate springanodize stand-offoxide fastener

Surface Treatment Specification:

Mil-c-13924, cl2 military specification 1st treatment response spring or qq-p-35 federal specification 2nd treatment response springmil-a-8625, ty2, cl2 military specification single treatment response stand-offmil-c-13924, cl2 military specification single treatment response fastener

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

Mil-std (military Standard):

Mil-c-13924 spec.