NSN 5305-01-344-4326

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-344-4326 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.287 inches and 0.337 inches **Fastener Length:** Between 0.359 inches and 0.389 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.297 inches and 0.301 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-01-344-4326

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0