

View Online at <https://aerobasegroup.com/nsn/5305-01-344-8409>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.717 inches and 0.810 inches

Fastener Length:

Between 0.780 inches and 0.810 inches

Head Style:

Pan

Head Diameter:

Between 0.594 inches and 0.615 inches

Head Height:

0.227 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Screw Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Screw Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas605 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.