NSN 5305-01-345-2442

Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-345-2442

Thread Class: 3a
Thread Direction:
Right-hand
Thread Length: 0.998 inches
Fastener Length: Between 1.045 inches and 1.075 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.344 inches and 0.385 inches
Shank Unthreaded Hole Diameter:
0.072 inches first hole and 0.081 inches first hole
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
Between 0.115 inches and 0.135 inches
Thready Qty Per Inch (tpi):
32
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center:
Distance From Head Largest Bearing Surface To Shank Hole Center:
Distance From Head Largest Bearing Surface To Shank Hole Center: 0.950 inches first hole
Distance From Head Largest Bearing Surface To Shank Hole Center: 0.950 inches first hole Material:
Distance From Head Largest Bearing Surface To Shank Hole Center: 0.950 inches first hole Material: Steel
Distance From Head Largest Bearing Surface To Shank Hole Center: 0.950 inches first hole Material: Steel Surface Treatment:
Distance From Head Largest Bearing Surface To Shank Hole Center: 0.950 inches first hole Material: Steel Surface Treatment: Cadmium and chromate
Distance From Head Largest Bearing Surface To Shank Hole Center: 0.950 inches first hole Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification:
Distance From Head Largest Bearing Surface To Shank Hole Center: 0.950 inches first hole Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response
Distance From Head Largest Bearing Surface To Shank Hole Center: 0.950 inches first hole Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator:
Distance From Head Largest Bearing Surface To Shank Hole Center: 0.950 inches first hole Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator: Unf
Distance From Head Largest Bearing Surface To Shank Hole Center: 0.950 inches first hole Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator: Unf Shelf Life:
Distance From Head Largest Bearing Surface To Shank Hole Center: 0.950 inches first hole Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator: Unf Shelf Life: N/a
Distance From Head Largest Bearing Surface To Shank Hole Center: 0.950 inches first hole Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:
Distance From Head Largest Bearing Surface To Shank Hole Center: 0.950 inches first hole Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:
Distance From Head Largest Bearing Surface To Shank Hole Center: 0.950 inches first hole Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No
Distance From Head Largest Bearing Surface To Shank Hole Center: 0.950 inches first hole Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No
Distance From Head Largest Bearing Surface To Shank Hole Center: 0.950 inches first hole Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No