NSN 5305-01-345-2460

Panel Screw Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-345-2460 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.235 inches and 0.265 inches **Fastener Length:** Between 0.485 inches and 0.515 inches **Head Style:** Drive **Head Diameter:** Between 0.297 inches and 0.327 inches **Head Height:** 0.110 inches **Internal Drive Style:** Hexagon **Material Accommodated Thickness:** 0.040 inches **Thread Diameter:** 0.138 inches Width Across Flats: 0.078 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 spring or steel comp 303 plus x spring or steel comp 303cu spring or steel comp 303ma spring or steel comp 303pb spring or steel comp 303se springsteel comp 303 stand-off or steel comp 303 plus x stand-off or steel comp 303cu stand-off or steel comp 303ma stand-off or steel comp 303pb stand-off or steel comp 303se stand-offiron alloy 660 fastener **Material Specification:** Ams5737 assn standard single material response fastener **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Fiig: A003b0

No

Demilitarization: