## NSN 5305-01-345-4008

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-345-4008 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.117 inches and 1.250 inches **Fastener Length:** Between 1.188 inches and 1.250 inches **Head Style:** Pan **Head Diameter:** Between 0.367 inches and 0.375 inches **Head Height:** Between 0.133 inches and 0.150 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams5737 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Bearing Surface Of Head Surface Finish:** 32.0 microinches **Thread Surface Finish:** 

32.0 microinches **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1101 professional/industrial association standard Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5305-01-345-4008

Machine Screw - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A500d0