

View Online at <https://aerobasegroup.com/nsn/5305-01-346-2261>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

5.250 inches

**Fastener Length:**

5.500 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 1.479 inches and 1.500 inches

**Head Height:**

Between 0.988 inches and 1.000 inches

**Locking Feature:**

Pellet threads or strip threads or patch threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

1.000 inches

**Width Across Flats:**

0.750 inches

**Thready Qty Per Inch (tpi):**

8

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

37.0 rockwell c fastener and 45.0 rockwell c fastener

**Material:**

Plastic polyamide locking feature steel uns k03104 fastener

**Material Specification:**

Astm a574 assn standard single material response fastener

**Surface Treatment:**

Aluminum fastener and chromate fastener or zinc fastener and chromate fastener

**Surface Treatment Specification:**

Mil-c-83488 type 2 cl 3 military specification 1st treatment response fastener or mil-c-87115 cl 3 military specification 2nd treatment response fastener

**Thread Series Designator:**

Unrc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-83488 spec.