

View Online at <https://aerobasegroup.com/nsn/5305-01-346-2263>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

2.500 inches

Fastener Length:

6.000 inches

Head Style:

Flat chamfer

Head Diameter:

Between 1.479 inches and 1.500 inches

Head Height:

Between 0.988 inches and 1.000 inches

Locking Feature:

Patch threads or strip threads or pellet threads

Internal Drive Style:

Hexagon

Thread Diameter:

1.000 inches

Width Across Flats:

Between 0.750 inches and 0.757 inches

Thready Qty Per Inch (tpi):

8

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

33.0 rockwell c fastener and 42.0 rockwell c fastener

Minimum Yield Strength:

120000 pounds per square inch

Material:

Plastic polyamide locking feature iron alloy 660 fastener

Material Specification:

Ams5731 assn standard single material response fastener or ams5737 assn standard single material response fastener

Precious Material And Location:

Fastener silver

Precious Material:

Silver

Surface Treatment:

Silver fastener

Surface Treatment Specification:

Ams2411 assn standard single treatment response fastener

Thread Series Designator:

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0