NSN 5305-01-346-2385



Externally Relieved Body Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-346-2385 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.203 inches **Fastener Length:** 0.565 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.238 inches and 0.279 inches **First Diameter From Head:** Between 0.099 inches and 0.101 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.422 inches **Point Style:** Flat **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity:** Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 348 or steel comp 384 or steel comp comp 385 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35, type 1, 2, 3, or 6 federal specification single treatment response **Thread Series Designator:** Unc

No

Shelf Life:

Unit Of Measure:

Demilitarization:

N/a

NSN 5305-01-346-2385

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0