## NSN 5305-01-346-3742

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-346-3742 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.406 inches **Fastener Length:** Between 1.079 inches and 1.109 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.297 inches and 0.302 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** 0.688 inches **Features Provided:** Cetyl alcohol lubricant Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment:** Aluminum and chromate **Surface Treatment Specification:** Amil-c-83488 type 2 cl 3 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-346-3742

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.