NSN 5305-01-346-3755

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-346-3755

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.469 inches |
| Fastener Length: |
| Between 1.391 inches and 1.421 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.390 inches and 0.395 inches |
| Grip Diameter: |
| Between 0.2485 inches and 0.2495 inches |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| 0.938 inches |
| Features Provided: |
| Cetyl alcohol lubricant |
| Thready Qty Per Inch (tpi): |
| 28 |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads |
| Material: |
| Steel comp xm-13 |
| Material Specification: |
| Ams 5629 assn standard single material response |
| Surface Treatment: |
| Aluminum and chromate |
| Surface Treatment Specification: |
| Mil-c-83488 type 2 cl 3 military specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |

NSN 5305-01-346-3755

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.