

View Online at <https://aerobasegroup.com/nsn/5305-01-346-5311>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.469 inches

Fastener Length:

Between 1.266 inches and 1.296 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.390 inches and 0.395 inches

Shoulder Diameter:

0.2641 inches first shoulder and 0.2651 inches first shoulder

Shoulder Length:

0.802 inches first shoulder and 0.822 inches first shoulder

Internal Drive Style:

High-torque

Thread Diameter:

0.250 inches

Features Provided:

Cetyl alcohol lubricant

Thready Qty Per Inch (tpi):

28

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Shoulder Shape:

Round first shoulder

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Aluminum and chromate

Surface Treatment Specification:

Mil-c-83488 type 2 cl 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.