

NSN 5305-01-347-9028 Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-347-9028 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.819 inches **Fastener Length:** Between 0.985 inches and 1.015 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.461 inches and 0.507 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Iron alloy 660

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416, ty2 cl2 federal specification single treatment response

Bearing Surface Of Head Surface Finish:

32.0 microinches

Shank Surface Finish:

32.0 microinches

Thread Surface Finish:

32.0 microinches

Thread Series Designator:

Unjf

Specification Data:

80205-nas1219 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-347-9028

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0