NSN 5305-01-347-9028

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-347-9028

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.819 inches
Fastener Length:
Between 0.985 inches and 1.015 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.461 inches and 0.507 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Screw Material:
Iron alloy 660
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416, ty2 cl2 federal specification single treatment response
Bearing Surface Of Head Surface Finish:
32.0 microinches
Shank Surface Finish:
32.0 microinches
Thread Surface Finish:
32.0 microinches
Thread Series Designator:
Unjf
Specification Data:
80205-nas1219 professional/industrial association standard
Shelf Life:
N/a
Unit Of Maagura

Unit Of Measure:

NSN 5305-01-347-9028

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

