## NSN 5305-01-347-9030

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-347-9030



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 1.045 inches and 1.124 inches Fastener Length: Between 1.109 inches and 1.156 inches **Head Style:** Hexagon **Head Height:** Between 0.105 inches and 0.120 inches Width Between Flats: Between 0.305 inches and 0.314 inches Hole Diameter: Between 0.046 inches and 0.056 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches **Hole Quantity:** 3 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Steel comp e4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5000 military specification 1st material response or -1I-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response Head Hole Configuration Style: Hexagon corners **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1801 professional/industrial association standard Shelf Life:

N/a

## NSN 5305-01-347-9030

Machine Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5000 spec.

