## NSN 5305-01-347-9777

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-347-9777 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.203 inches and 0.218 inches **Fastener Length:** Between 0.735 inches and 0.765 inches **Head Style:** Knurled no. 5 **Head Diameter:** Between 0.266 inches and 0.281 inches **Head Height:** Between 0.302 inches and 0.322 inches Point Length: 0.094 inches **Point Diameter:** Between 0.085 inches and 0.101 inches **First Diameter From Head:** Between 0.085 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.427 inches and 0.447 inches Point Style: Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** Between 85.0 degrees and 95.0 degrees Material: Steel **Material Specification:** Astm-a-581 assn standard single material response or astm-a-582 assn standard single material response **Surface Treatment: Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

## NSN 5305-01-347-9777

Externally Relieved Body Screw - Page 2 of 2



Inread Series Designator
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0