## NSN 5305-01-348-0150

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-348-0150



## Thread Class:

3a

**Thread Direction:** 

Right-hand

#### Thread Length:

Between 1.482 inches and 1.561 inches

#### Fastener Length:

Between 1.546 inches and 1.593 inches

#### Head Style:

Hexagon

Head Height:

Between 0.105 inches and 0.120 inches

#### Width Between Flats:

Between 0.305 inches and 0.314 inches

#### Internal Drive Style:

Cross recess type 1

#### Thread Diameter:

0.190 inches

#### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Screw Material:

Steel comp e4340 or steel comp 8740

#### Screw Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response

#### **Screw Surface Treatment:**

Cadmium and chromate

#### Screw Surface Treatment Specification:

Qq-p-416 ty2 cl2 federal specification single treatment response

#### Thread Series Designator:

Unjf

#### **Specification Data:**

80205-nas1801 professional/industrial association standard

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

### Fiig:

A500d0

# NSN 5305-01-348-0150

Machine Screw - Page 2 of 2

### Mil-std (military Standard):

Mil-s-5000 spec.

