Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-348-0782

2a Thread Direction: Right-hand Thread Length: Between 0.235 inches and 0.255 inches Fastener Length: 0.625 inches Head Style: Read Style: Flat countersunk Head Diameter: Between 0.183 inches and 0.225 inches First Diameter From Head: Between 0.085 inches and 0.225 inches First Diameter From Head: Between 0.085 inches and 0.290 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.270 inches and 0.290 inches Internal Drive Style: Cross recess type 1
Right-handThread Length:Between 0.235 inches and 0.255 inchesFastener Length:0.625 inchesHead Style:Flat countersunkHead Diameter:Between 0.183 inches and 0.225 inchesFirst Diameter From Head:Between 0.085 inches and 0.089 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:Between 0.270 inches and 0.290 inchesInternal Drive Style:Cross recess type 1
Thread Length: Between 0.235 inches and 0.255 inches Fastener Length: 0.625 inches Head Style: Flat countersunk Head Diameter: Between 0.183 inches and 0.225 inches First Diameter From Head: Between 0.085 inches and 0.089 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.270 inches and 0.290 inches Internal Drive Style: Cross recess type 1
Thread Length: Between 0.235 inches and 0.255 inches Fastener Length: 0.625 inches Head Style: Flat countersunk Head Diameter: Between 0.183 inches and 0.225 inches First Diameter From Head: Between 0.085 inches and 0.089 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.270 inches and 0.290 inches Internal Drive Style: Cross recess type 1
Between 0.235 inches and 0.255 inches Fastener Length: 0.625 inches Head Style: Flat countersunk Head Diameter: Between 0.183 inches and 0.225 inches First Diameter From Head: Between 0.085 inches and 0.089 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.270 inches and 0.290 inches Internal Drive Style: Cross recess type 1
0.625 inches Head Style: Flat countersunk Head Diameter: Between 0.183 inches and 0.225 inches First Diameter From Head: Between 0.085 inches and 0.089 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.270 inches and 0.290 inches Internal Drive Style: Cross recess type 1
0.625 inches Head Style: Flat countersunk Head Diameter: Between 0.183 inches and 0.225 inches First Diameter From Head: Between 0.085 inches and 0.089 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.270 inches and 0.290 inches Internal Drive Style: Cross recess type 1
Flat countersunkHead Diameter:Between 0.183 inches and 0.225 inchesFirst Diameter From Head:Between 0.085 inches and 0.089 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:Between 0.270 inches and 0.290 inchesInternal Drive Style:Cross recess type 1
Head Diameter: Between 0.183 inches and 0.225 inches First Diameter From Head: Between 0.085 inches and 0.089 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.270 inches and 0.290 inches Internal Drive Style: Cross recess type 1
Between 0.183 inches and 0.225 inches <b>First Diameter From Head:</b> Between 0.085 inches and 0.089 inches <b>Distance From Largest Bearing Surface Of Head To End Of First Diameter:</b> Between 0.270 inches and 0.290 inches <b>Internal Drive Style:</b> Cross recess type 1
First Diameter From Head: Between 0.085 inches and 0.089 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.270 inches and 0.290 inches Internal Drive Style: Cross recess type 1
Between 0.085 inches and 0.089 inches <b>Distance From Largest Bearing Surface Of Head To End Of First Diameter:</b> Between 0.270 inches and 0.290 inches <b>Internal Drive Style:</b> Cross recess type 1
Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.270 inches and 0.290 inches Internal Drive Style: Cross recess type 1
Between 0.270 inches and 0.290 inches Internal Drive Style: Cross recess type 1
Internal Drive Style: Cross recess type 1
Cross recess type 1
Thready Qty Per Inch (tpi):
12
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 4037 or steel comp 8630
Material Specification:
Mil-s-6050 military specification 1st material response or ams6300 assn standard 2nd material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416 type 1 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0



Mil-std (military Standard):

Mil-s-6050 spec.