NSN 5305-01-348-0782

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-348-0782 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.235 inches and 0.255 inches **Fastener Length:** 0.625 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.183 inches and 0.225 inches First Diameter From Head: Between 0.085 inches and 0.089 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.270 inches and 0.290 inches **Internal Drive Style:** Cross recess type 1 Thready Qty Per Inch (tpi): 12 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 4037 or steel comp 8630 **Material Specification:** Mil-s-6050 military specification 1st material response or ams6300 assn standard 2nd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 type 1 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A003b0

NSN 5305-01-348-0782

Externally Relieved Body Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.