NSN 5305-01-348-2677

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-348-2677

Thread Class.
Thread Class:
3a Three I Directions
Thread Direction:
Right-hand
Thread Length:
0.375 inches
Fastener Length:
Between 0.485 inches and 0.515 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.429 inches and 0.438 inches
Head Height:
Between 0.162 inches and 0.183 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Internal Drive Style:
Torque-set ribbed
Thread Diameter:
0.312 inches
Grip Length:
Between 0.115 inches and 0.135 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Material:
Steel comp 4140 or steel comp e4340 or steel comp 8740
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1125 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-01-348-2677

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0