NSN 5305-01-348-2678

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-348-2678

Thread Class
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.276 inches
Fastener Length:
Between 0.573 inches and 0.603 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.221 inches and 0.226 inches
Head Height:
Between 0.074 inches and 0.086 inches
Grip Diameter:
Between 0.1365 inches and 0.1375 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.138 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Date:

Specification Data:

80205-nas1121 professional/industrial association standard

NSN 5305-01-348-2678

Close Tolerance Screw - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0