NSN 5305-01-348-2681

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-348-2681 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.276 inches **Fastener Length:** Between 3.511 inches and 3.541 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.306 inches and 0.313 inches **Head Height:** Between 0.103 inches and 0.118 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 3.240 inches and 3.260 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Surface Finish:** 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Steel comp 4140 or steel comp e4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1123 professional/industrial association standard Shelf Life:

N/a

NSN 5305-01-348-2681

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0