NSN 5305-01-348-2683

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-348-2683 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.276 inches **Fastener Length:** Between 0.699 inches and 0.729 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.328 inches and 0.385 inches **Grip Diameter:** Between 0.1881 inches and 0.1887 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material: Titanium alloy uns r56400 **Material Specification:** Ams 4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1153 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-348-2683

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0