## NSN 5305-01-348-2684

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-348-2684 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.781 inches **Fastener Length:** Between 2.953 inches and 2.999 inches **Head Style:** Hexagon **Head Height:** Between 0.265 inches and 0.297 inches Width Between Flats: Between 0.740 inches and 0.752 inches **Grip Diameter:** Between 0.4986 inches and 0.4991 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.500 inches **Grip Length:** Between 2.187 inches and 2.202 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Surface Finish:** 32.0 microinches bearing surface of head32.0 microinches grip Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unf Shelf Life:

N/a **Unit Of Measure:** 

## NSN 5305-01-348-2684

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.