NSN 5305-01-348-8440

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-348-8440 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.240 inches **Fastener Length:** 0.640 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches First Diameter From Head: 0.164 inches **Second Diameter From Head:** 0.120 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.060 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.460 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 305 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel co steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 361 or steel comp comp 385 **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a

Unit Of Measure:

Demilitarization:

NSN 5305-01-348-8440

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0