NSN 5305-01-348-8463

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-348-8463

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.545 inches
Fastener Length:
Between 0.595 inches and 0.625 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.176 inches and 0.183 inches
Head Height:
Between 0.108 inches and 0.112 inches
Hole Diameter:
Between 0.033 inches and 0.039 inches
Locking Feature:
Patch threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.112 inches
Width Across Flats:
Between 0.0937 inches and 0.0952 inches
Hole Quantity:
2
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Material:
Plastic polyamide locking featureiron alloy 660 fastener
Material Specification:
Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

NSN 5305-01-348-8463

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A003b0